DC Brushed Torque Motor type : TQRB-15-0.39



Performance Data			
Parameter	Simbol	Units	Value
Peak Torque, stalled @Vp	Tp	mNm	77.7
Power Input @Tp	P	W	56.7
Motor Constant	Km	$mNm/\sqrt{W}$	10.3
Electrical Time Constant	Te	ms	0.17
No Load Speed Theoretical @ Vp	ω_{NLT}	rpm	6962
Break Away Torque	Tf	mNm	4.24
Ripple Torque	T_R	% (avg to peak)	7
Maximum Allowable Temperature	Temp.	°C (at winding)	155
Thermal Resistence	tpr	°C/W	25
Weight	WT	g	46.8
Rotor Inertia	Jm	Kg m^2	$2.97*10^{-6}$

Winding Constants				
Parameter	Simbol	Units	Tolerance	Value
D.C. Resistance	R	Ω	±12.5%	5.9
Inductance	L	mH	±30%	1
Torque Sensitivity	Kt	mNm/A	±10%	25.1
Back EMF Constant	Kb	V/(rad/sec)	±10%	0.0251
Peak Voltage @ Tp	Vp	V	Nominal	18.3
Peak Current @ Tp	Ip	A	Nominal	3.1

Leads AWG 26 teflon coated; 300 mm minimum length.
Direction of rotation viewed from brush end, CW when a positive voltage is applied to the orange lead rel to the green.
Insulation resistance @ 250 V D.C., min 100 MΩ.
Dielectric withstanding voltage - withstand at 250 V rms; 50 Hz ; 1 minute between either lead and armature.
All measurements are made at 25 °C ambient temperature.
Mounting dimensions and color of wires can be changed in conformity with customer requirement.

icpe www.icpe.ro e-mail: office@icpe.ro
phone: +40 21 589 33 00 fax: +40 21 589 34 34
icpe C4 –messico www.icpe.ro/messico e-mail: messico@icpe.ro
phone: +40 21 589 34 09 fax: +40 21 346 72 90