DC Brushed Torque Motor type : TQRB-51-1.00



Performance Data			
Parameter	Simbol	Units	Value
Peak Torque, stalled @Vp	Tp	Nm	4.8
Power Input @Tp	P	W	96
Motor Constant	Km	$Nm/\sqrt{W}$	0.49
Electrical Time Constant	Te	ms	0.8
No Load Speed Theoretical @ Vp	ω_{NLT}	rpm	191
Break Away Torque	Tf	mNm	100
Ripple Torque	T_R	% (avg to peak)	7
Maximum Allowable Temperature	Temp.	°C (at winding)	155
Thermal Resistence	tpr	°C/W	2.5
Weight	WT	g	920
Rotor Inertia	Jm	Kg m^2	$2.25*10^{-3}$

Winding Constants				
Parameter	Simbol	Units	Tolerance	Value
D.C. Resistance	R	Ω	±12.5%	6
Inductance	L	mH	±30%	4.8
Torque Sensitivity	Kt	Nm/A	±10%	1.2
Back EMF Constant	Kb	V/(rad/sec)	±10%	1.2
Peak Voltage @ Tp	Vp	V	Nominal	24
Peak Current @ Tp	Ip	A	Nominal	4

Leads AWG 24 teflon coated; 300 mm minimum length.
Direction of rotation viewed from brush end, CW when a positive voltage is applied to the red lead relative to the black.
Insulation resistance @ 250 V D.C., min 50 MΩ.
All measurements are made at 25 °C ambient temperature.
Mounting dimensions and color of wires can be changed in conformity with customer requirement..

icpe S.A. www.icpe.ro e-mail: office@icpe.ro
phone: +40 21 589 33 00 fax: +40 21 589 34 34
icpe C4 –messico www.icpe.ro/messico e-mail: messico@icpe.ro
phone: +40 21 589 34 09 fax: +40 21 346 72 90